

Forklift



Model: CDMxxD

CDMxxD forklift is a mechanical, internal combustion powered, counterbalanced forklift family. "xx" stands for rated payload. Currently available models are CDM20D, CDM25D, CDM30D and CDM35D. Our forklift has become an indispensable piece of construction equipment in manufacturing and warehousing operations.

Features of CDMxxD Forklift:

1. Suspension shockproof engine mounting, spring connected steering axle, easier turning in small radius.
2. Waterproof electrical connectors and multiple fuses ensure the safety of electrical system.
3. Adjustable steering column, precision gauges, clear reading, easy operation.
4. Lifting system of this forklift adopts wide view mast to improve operator's visibility.
5. Pipelines are with safety device for blocking the mast in case of pipe damage.
6. Optional attachment: side shifter, tyre clamp, paper-roll clamp, bale clamp, fork, etc.
7. Other options for this forklift: enclosed cabin, fire extinguisher, solid tyre, tyre protector

Specifications of CDM20D/CDM25D/CDM30D/CDM35D Forklift:

Model	CDM20D Forklift	CDM25D Forklift	CDM30D Forklift	CDM35D Forklift
Power type	Diesel			
Rated capacity(kg)	2000	2500	3000	3500
Load center(mm)	500	500	500	500
Max.lift height(standard mast) (mm)	3000	3000	3000	3000
Free lift height(mm)	140	140	188	165
Fork size(mm)	970×122×40	1070×122×40	1070×125×45	1070×150×45
Mast tilt angle(°)	6/12	6/12	6/12	6/12
Turning radius(mm)	2265	2310	2450	2520
Front overhang(mm)	460	460	483	493

Grade ability(Full load)(%)	20	20	20	18
Self weight(kg)	3270	3580	4031	4700
Tread (Front/Rear)(mm)	960/970	960/970	1000/970	1000/970
Min.right angle aisle width(mm)	4163	4238	4155	4283
Wheel base(mm)	1600	1600	1700	1700
Overall length(mm)	3410	3590	3775	3830
Overall width(mm)	1150	1150	1225	1238
Mast lowered height(mm)	2030	2030	2077	2175
Overhead guard height(mm)	2079	2079	2100	2130
Travel speed(Kw/h)	22/22	22/22	20/20	18.5/20
Max lift speed(No load/Full load)(mm/s)	530/500	530/500	430/410	420/400