



### Model: CDMxxDT (Diesel Forklift)

CDMxxDT forklift is a hydraulically torque converted, internal combustion powered, counterbalanced forklift family. "xx" refers to rated payload. Currently available models are CDM20DT, CDM25DT, CDM30DT, CDM35DT, CDM50DT, CDM60DT and CDM70DT. Our diesel forklift becomes the engineering vehicle/construction vehicle that is widely used all over the world.

### Features of CDMxxDT Forklift:

1. Hydraulic torque converter for stepless gear change and high efficiency
2. Suspension shockproof engine mounting, spring connected steering axle, easier turning in small radius
3. Waterproof electrical connectors and multiple fuses ensure the safety of electrical system
4. Adjustable steering column of CDMxxDT forklift, easy operation, precision gauges, clear reading
5. Wide view mast is with lifting system to improve operator's visibility
6. Pipelines are with safety device for blocking the mast in case of pipe damage
7. Optional attachment: side shifter, tyre clamp, paper-roll clamp, bale clamp, fork, etc.
8. Other options of this forklift: enclosed cabin, fire extinguisher, solid tyre, tyre protector

### Specifications of CDM20DT/CDM25DT/CDM30DT/CDM35DT/CDM50DT/CDM60DT/CDM70DT Forklift

| Model                               | CDM20DT<br>Forklift | CDM25DT     | CDM30DT     | CDM35DT<br>Forklift | CDM50DT     | CDM60DT     | CDM70DT<br>Forklift |
|-------------------------------------|---------------------|-------------|-------------|---------------------|-------------|-------------|---------------------|
| Power type                          | Diesel              |             |             |                     |             |             |                     |
| Rated capacity(kg)                  | 2000                | 2500        | 3000        | 3500                | 5000        | 6000        | 7000                |
| Load center(mm)                     | 500                 | 500         | 500         | 500                 | 600         | 600         | 600                 |
| Max.lift height (standard mast)(mm) | 3000                | 3000        | 3000        | 3000                | 3000        | 3000        | 3000                |
| Free lift height(mm)                | 140                 | 140         | 164         | 165                 | 200         | 205         | 210                 |
| Fork size(mm)                       | 970x122x40          | 1070x122x40 | 1070x125x45 | 1070x150x45         | 1220x150x55 | 1070x150x65 | 1220x150x65         |